

Vivitek D863

Versatile projector with
embedded media player



Product Features

- 3,000 ANSI lumens of brightness with a 15,000:1 contrast
- DLP® and BrilliantColor™ technologies from Texas Instruments
- XGA (1024 x 768) resolution with a maximum resolution up to UXGA (1600 x 1200)
- Powerful and easy to use multimedia utility (application) allows the projector to be controlled and monitored through a PC with a USB or network connection (RJ-45)
- Integrated media and document viewer conveniently plays documents, photos, videos and audio files without the need to connect a PC
- Assortment of connectivity options for easy connection to a variety of multimedia devices (HDMI, VGA, USB)
- 3D Ready through DLP-Link
- Top-loading, sliding cover for quick and easy lamp replacement
- Built-in 10W audio speaker
- Sealed optical engine, minimizing the impact of dust and smoke
- Security solutions include: Kensington® security slot, security bar, keypad lock

Product Photos

Product Specifications		
Display Type	DLP	
Brightness	3000 ANSI Lumens	
Native Resolution	XGA (1024 x 768)	
Maximum Resolution	Up to UXGA (1600 x 1200)@60Hz	
Contrast Ratio	15,000:1	
Lamp Life and Type	4500/6000 Hours (Boost / Std. Mode), 190W	
Throw Ratio	1.6 - 1.92:1	
Image Size (Diagonal)	25.6"-308"	
Projection Distance	1 - 10 m	
Projection Lens	F=2.50~2.72, f = 17.81~21.35mm	
Zoom Ratio	1.2x	
Aspect Ratio	4:3 Native, 16:9 and 16:10 Compatible	
Offset	128% +/-10%	
Keystone Correction	Vertical +/- 40 steps	
Horizontal Frequency	15, 30 - 90KHz	
Vertical Scan Rate	43 - 120Hz	
Speakers	10W	
3D Ready	Yes (Via DLP Link)	
Lens Shift Range	N/A	
Video Compatibility	SDTV(480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i/p), NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, K1, L)	
File Formats Supported	Documents	Microsoft® Office 97 - 2007 (DOC, PPT, XLS), Adobe® Reader (PDF), Text (TXT)
	Video	AVI, DIVX, MKV, TS, DAT, VOD, MPG, MPEG, MOV, MP4, RM, RMVB, WMV
	Image	JPEG, JPG, BMP
	Audio	MP1, MP2, MP3, WMA, OGG, ADPCM-WAV, PCM-WAV, AAC
I/O Connection Ports	HDMI v1.3, VGA-In (x2), Composite Video, Audio-In RCA(L/R), Audio-In (Mini-Jack), VGA-Out, USB (Type A)(x2), Audio-Out (Mini-Jack), RJ45, RS-232C, Mini-USB (Service)	
Projection Method	Table Top, Ceiling Mount (Front or Rear)	
Security Solutions	Kensington® Security Slot, Security Bar, Keypad Lock	
Dimensions (W x D x W)	285 x 261 x 121.8 mm (11.22" x 10.3" x 4.8")	
Weight	2.7kg	
Noise Level	32dB/34dB (Std./Boost Mode)	
Power Supply	AC 100-240V, 50/60Hz	
Power Consumption	260 W (Boost Mode), 230 W (Std. Mode), <0.5W (Standby Mode)	
Standard Accessories	AC Power Cord, VGA Cable, Carrying Case, Remote Control, Lens Cap, Documentation Kit	
Optional Accessories	Replacement Lamp, Remote, Carrying Case	

©2012 Vivitek Corporation. Vivitek is a trademark of Vivitek Corporation. Other trademarks are the properties of their respective owners. Values, weights and dimensions shown are approximate. Errors and omissions accepted. Specifications are subject to change without prior notice.

