



## Maintenance-Free Laser Projector

### FEATURES

- Ultra short throw lens to make 150 inch big screen at only 40cm away
- 3,500 ANSI lumens of brightness, WXGA resolution and 12,000:1 contrast ratio for clear, crisp and bright projection
- Maintenance-free laser light source for up to 20,000 hours operation
- 10W speaker and multiple audio ports for external sound device
- Image adjustment with 4 corner correction
- Network ready for integration and system administration via RJ45



## Ultra Short Throw with up to 150 inch screen size

The DW763Z-UST is designed for large screen displays at museum, in education or showroom applications where installation space is a constraint. Features a WXGA (1280 x 800), an amazing 3,500 Ansi Lumens and 12,000:1 contrast ratio for a clear and bright projection. In addition to this, the device is maintenance free, thanks to their lamp less laser light source design, which delivers up to 20,000 hours of operational time.



## DW763Z-UST SPECIFICATIONS

Image	<b>Display Type</b>	Single chip DLP® Technology by Texas Instruments
	<b>Brightness</b>	3500
	<b>Native Resolution</b>	WXGA (1280 x 800)
	<b>Max. Supported Resolution</b>	WUXGA (1920 x 1200) @60Hz
	<b>Native Aspect Ratio</b>	16:10
	<b>Contrast Ratio</b>	12,000:1
	<b>Keystone Correction</b>	Vertical: +/- 30°; Horizontal: +/- 30°
Optical	<b>Throw Ratio</b>	0.24:1
	<b>Zoom Ratio</b>	Fixed 1x
	<b>Image Size (Diagonal)</b>	80" - 150"
	<b>Projection Distance</b>	4 - 41 cm (from the screen to the projector)
	<b>Offset (Based on Full Image Height)</b>	115% from the lens center; 122% from the bottom of the projector
Features	<b>Features</b>	3D Ready(DLP link, PC+Video), Direct 3D (HDMI 1.4a), 3D Mandatory Formats supported (top/bottom, right/left, frame sequential), Keypad lock
Compatibility	<b>Video</b>	SDTV (480i, 576i) / EDTV (480p, 576p) / HDTV (720p, 1080i, 1080p), NTSC (M, 3.58/4.43 MHz), PAL (B,D,G,H,I,M,N) SECAM (B,D,G,K,K1,L)
Connectivity	<b>I/O Connection Ports</b>	VGA-In (15pin D-Sub), HDMI (x2), S-Video, Composite Video, Audio-In (RCA) , Audio-In (Mini-Jack), VGA-Out (15pin D-Sub), Audio-Out (Mini-Jack), RJ45, RS-232, USB A (Power Only), USB miniB (Service)
General	<b>Dimensions (W x D x H)</b>	509 x 390 x 145 mm
	<b>Weight</b>	10.5
	<b>Power</b>	Supply: AC 100-240V, 50/60Hz Consumption: 315W (Eco. Mode), 380W (Normal Mode), <0.5W (Standby)
	<b>Lamp Life and Type</b>	Lamp free design. Laser light source last up to 20,000 hours
	<b>Speakers</b>	10W
	<b>Noise Level</b>	31dB / 28dB (Normal / Eco. Mode)
	<b>Standard Accessories</b>	VGA Cable, User Manual (CD), Quick Start Guide, Warranty Card (by region), Remote Controller (with battery), AC Power Cord
	<b>Optional Accessories</b>	Remote Control P/N (tbc)
	<b>Warranty</b>	Ultra Short Throw Laser Phosphor Warranty
	<b>UPC Code</b>	813097022592