



## XGA Versatile Installation Projector

### FEATURES

- XGA resolution (1024 x 768)
- 6000 ANSI Lumens and 10.000:1 contrast ratio
- DLP<sup>®</sup> and BrilliantColor<sup>™</sup> technologies for detailed image quality
- Centered lens for easy planning & installation
- 1,7x optical zoom and Manual horizontal and vertical lens shift
- HDMI and DVI-D connectors for high quality digital video signals
- Digital vertical & horizontal keystone, warp and individual corner adjustments
- MHL device compatibility for streaming of video and audio content from a compatible mobile device
- PC-Free presentation using JPG picture reader from USB thumb drive
- Wireless presentation streaming with optional WiFi dongle
- Audio ready with 2 x 7W stereo speakers with Surround emulation, 3 x 3,5mm Jack inputs and 1 x 3,5mm jack out. 3.5mm Jack microphone input
- Built-in 12V trigger for screen and/or blinds control



The DX3351 offers great features and performance combined with great installation flexibility. The 6,000 ANSI lumens make it bright enough for larger screens, and the wide screen XGA native image resolution ensures that your content will be delivered with fidelity and sufficient detail for a wide range of applications. The 1,3-2,2:1 Throw Ratio makes it possible to install the projector in a wide range of distances, making installation planning easier whether you replace an older projector or making a new installation. The 1,7x zoom range and horizontal and vertical lens shift gives further flexibility when installing the projector. Featuring 3D and an extensive in/output panel ensures the projector is suited for retrofit as well as new installations.

# DX3351

## MULTIMEDIA



## SPECIFICATIONS



<b>Display Type</b>	Single 0.7" DLP Technology by TI
<b>Brightness</b>	6,000 ANSI Lumens
<b>Native Resolution</b>	XGA (1024 x 768)
<b>Maximum Resolution</b>	WUXGA (1920x1200) @60Hz
<b>Contrast Ratio</b>	10,000:1
<b>Lamp Life and Type</b>	1,500/ 3,500 Hours (Normal/Eco. Mode), 370W/280W Osram
<b>Throw Ratio</b>	1.3~2.2:1
<b>Image Size (Diagonal)</b>	23"~378"
<b>Projection Distance</b>	1~ 10m
<b>Projection Lens</b>	F=2.45~ 3.22, f=18.8mm~32mm
<b>Zoom Ratio</b>	1.7x
<b>Aspect Ratio</b>	4:3
<b>Offset (full image height)</b>	Manual Lens Shift
<b>Keystone Correction</b>	Vertical: +/-30° Horizontal: +/- 25°
<b>Speakers</b>	7W RMS x 2
<b>3D Ready</b>	Yes (Supports DLP Link, Blu-ray 3D)
<b>Lens Shift Range</b>	Vertical: -10.5%,+3% Horizontal: +/-3.8%
<b>Video Compatibility</b>	SDTV (480i, 576i) / EDTV (480p, 576p) / HDTV (720p, 1080i, 1080p), NTSC (M, 3.58/4.43 MHz), PAL (B,D,G,H,I,M,N) SECAM (B,D,G,K,K1,L)
<b>I/O Connection Ports</b>	VGA-In (2x), HDMI/MHL, HDMI v1.4b, DVI-D, Component (5 BNC) (RGBHV), Audio-In (RCA), Audio-In (Mini-Jack)(3x), VGA-Out (15pin D-Sub), Audio-Out (RCA), Audio-Out (Mini-Jack), RJ-45 IP Telnet Capable Over RJ-45, 12v Trigger (3.5mm mini-jack), RS-232, 3D-Sync Out, USB type A (Wifi Dongle), USB miniB (Display), USB B (Service Only, Microphone (Mini-Jack), Remote Jack wire remote 1 in, 1 out (pass through)
<b>Projection Method</b>	Table Top, Ceiling Mount (Front or Rear)
<b>Security Solutions</b>	Kensington® Security Slot, Security Bar, Keypad Lock
<b>Dimensions (W x D x H)</b>	445 x 331 x 143 mm, (Height w/Foot 162 mm)
<b>Weight</b>	6,8 kg
<b>Noise Level</b>	39dB/33dB (Standard/Eco. Mode)
<b>Power</b>	AC Universal 100-240V/50-60hz, Consumption: 530W (Normal Mode) / 430W (Eco.Mode)
<b>Warranty</b>	3 years projector / 1 year on lamp or 1000 hours whichever comes first
<b>Standard Accesories</b>	AC Power Cord, VGA Cable, Remote Control, Filter, Documentation Kit
<b>Optional Accesories</b>	Replacement Lamp: 5811119760-SVV, Wireless USB Dongle
<b>UPC</b>	813097020383

© Copyright 2015 Vivitek. Vivitek is a registered trademark of Delta Electronics, Inc. DLP® and the DLP logo are registered trademarks of Texas Instruments. All specifications are subject to change at any time.

Vivitek EMEA, Zandsteen 15, 2132 MZ Hoofddorp, The Netherlands  
tel: +31 20 655 0960 | fax: +31 20 655 0999 | email: info@vivitek.eu